

## 3/8" FLEXAIR fully assembled polymer hose with prevoS1 quick coupling and plug



<u>ID (in)</u> 3/8"	<u>Coupler</u> ISI 06	<u>Plug</u> IRP 06	<u>Length (ft)</u> 25'
<u>Operating pressure</u> 29 to 174 psi	<u>Temperature</u> +5°F to +140°F	<u>Construction</u> PVC	<u>Equipped with</u> Coupler and adapter

Description				
Reference	ID (in)	Coupler	Plug	Length (ft)
RST RISB3825	3/8"	ISI 06	IRP 06	25'
RST RISB3835	3/8"	ISI 06	IRP 06	35'
RST RISB3850	3/8"	ISI 06	IRP 06	50'
RST RISB38100	3/8"	ISI 06	IRP 06	100'
RST RUSB3825	3/8"	USI 06	URP 06	25'

Reference	ID (in)	Coupler	Plug	Length (ft)
<b>RST RUSB3835</b>	3/8"	USI 06	URP 06	35'
<b>RST RUSB3850</b>	3/8"	USI 06	URP 06	50'
<b>RST RUSB38100</b>	3/8"	USI 06	URP 06	100'
<b>RST RESB3825</b>	3/8"	ESI 07	ERP 07	25'
<b>RST RESB3835</b>	3/8"	ESI 07	ERP 07	35'
<b>RST RESB3850</b>	3/8"	ESI 07	ERP 07	50'
<b>RST RESB38100</b>	3/8"	ESI 07	ERP 07	100'
<b>RST RASB3825</b>	3/8"	ASI 06	ARP 06	25'
<b>RST RASB3835</b>	3/8"	ASI 06	ARP 06	35'
<b>RST RASB3850</b>	3/8"	ASI 06	ARP 06	50'
<b>RST RASB38100</b>	3/8"	ASI 06	ARP 06	100'

