

# STOFLEX anti-static flexible rubber hose with prevoS1 quick safety coupler



<u>ID (in)</u> 3/8"	<u>Length (m)</u> 25'	<u>Coupler</u> ISI 061810	<u>Operating pressure</u> 29 to 174 psi
<u>Temperature</u> +5°F to +158°F			

Description							
Reference	ID (in)	Length (m)	Coupler	ID/OD (mm)	Profile	Adaptor	Equipped with
<b>RAL SISB3825</b>	3/8"	25'	ISI 061810	8 x 15	British	BRP 06	Protector
<b>RAL SBSB810</b>	3/8"	10	BSI 06	10 x 18	ISO 6150 B	IRP 06	Protector
<b>RAL SISB3835</b>	3/8"	35'	ISI 061810				

Reference	ID (in)	Length(m)	Coupler	ID/OD (mm)	Profile	Adaptor	Equipped with
RAL SISB3850	3/8"	50'	ISI 061810				
RAL SISB38100	3/8"	100'	ISI 061810				
RAL SESB3825	3/8"	35'	ESI 071810				
RAL SESB3835	3/8"	35'	ESI 071810				
RAL SISB1012	3/8"	12.5	ISI 06				
RAL SESB3850	3/8"	50'	ESI 071810				
RAL SESB38100	3/8"	100'	ESI 071810				
RAL SUSB3825	3/8"	25'	USI 061810				
RAL SUSB3835	3/8"	50'	USI 061810				
RAL SUSB3850		50'	USI 061810				
RAL SUSB38100		100'	USI 061810				

