

## PPS1 SKITVP - Pneumatic safety valve



<p><b><u>BSPP female thread</u></b> (1) 1/2" NPT</p>	<p><b><u>For pipe OD (in)</u></b> -</p>	<p><b><u>Technology</u></b> PPS Grip Concept</p>	<p><b><u>Operating pressure</u></b> 0 to 16 bar</p>
<p><b><u>Vacuum capability</u></b> -0.98 bar (vacuum 98%)</p>	<p><b><u>Temperature</u></b> -20°C to +80°C</p>	<p><b><u>Construction</u></b> Pipe and fittings: alu.</p>	<p><b><u>Highlight</u></b> Scalable system</p>
<p><b><u>Meets standards</u></b> PED REACH</p>			

Description		
Reference	BSPP female thread	For pipe OD (in)
PPS1 SKITVP203	(1) 1/2" NPT	-
PPS1 SKITVP204	(1) 3/4" NPT	-
PPS1 SKITVP205	(1) 1" NPT	-
PPS1 SKITVP40	-	(2) 1 1/2"
PPS1 SKITVP50	-	(2) 2"
PPS1 SKITVP63	-	(2) 2 1/2"
PPS1 SKITVP80	-	(2) 3"
PPS1 SKITVP100	-	(2) 4"

