

Options



<p>Description</p> <p>(1) Metal cover diam. 11 in</p>	<p>Technology</p> <p>Piston dual action</p>	<p>Operating pressure</p> <p>43 to 100 psi</p>	<p>Outlet pressure</p> <p>5800 psi (air pressure at 100 psi)</p>
<p>Flow rate</p> <p>300 z/min (for air pressure 87 psi)</p>	<p>BSPP female thread</p> <p>Air inlet : 1/4" FBSP</p>	<p>Pressure ratio</p> <p>58:1</p>	<p>BSPP male thread</p> <p>Grease outlet: G 1/4</p>

Description	
Reference	Description
EPG CV20	(1) Metal cover diam. 11 in

Reference	Description
EPG CV30	(1) Metal cover diam. 12.6 in
EPG CV60	(1) Metal cover diam. 15 in
EPG CV65	(1) Metal cover Ø 15 to 16 in
EPG MB20	(2) Sealing diaphragm Ø 9.4/10.2 in
EPG MB30	(2) Sealing diaphragm Ø 10.6/11.4 in for EPG KR30
EPG MB31	(2) Sealing diaphragm for drum Ø 11/11.8 in
EPG MB34	(2) Sealing diaphragm Ø 11.8/13 in
EPG MB60	(2) Sealing diaphragm Ø 13.2/14.2 in for EPG KR60
EPG MB65	(2) Sealing diaphragm Ø 14.6/15.7 in
EPG TC414	(3) Rubber hose 13 ft
EPG TC614	(3) Rubber hose 20 ft
EPG TC214	(3) Rubber hose for connecting pump to reel
EPG RT14	Sealing coupling
EPG SW14	(4) Universal joint sealing coupling
EPG PG	Carrying handle
EPG VS30	(5) 1.2 in bolt to hold pump in drum
EPG CA20	(6) Transport cart for 22/44 lb drums
EPG CAN60	(6) Transport cart for 44/66 lb

