

Polyurethane Ester base tubing in 328 ft rolls (unit of sales = 1 spool)



<u>ID (/OD (mm))</u> 2.5 x 4	<u>Mini bend radius (at 68° F (in))</u> 0.47	<u>Max operating pressure (at 68° F (psi))</u> 145	<u>Color</u> Black
<u>Temperature</u> - 4°F to +158°F	<u>Construction</u> Polyurethane Ester base	<u>Highlight</u> Resistant to oils and greases	

Description				
Reference	ID (/OD (mm))	Mini bend radius (at 68° F (in))	Max operating pressure (at 68° F (psi))	Color
PUBK M2504100	2.5 x 4	0.47	145	Black
PUBE M2504100	2.5 x 4	0.47	145	Blue

Reference	ID (/OD (mm))	Mini bend radius (at 68° F (in))	Max operating pressure (at 68° F (psi)	Color
PUCR M2504100	2.5 x 4	0.47	145	Clear
PUGN M2504100	2.5 x 4	0.47	145	Green
PUYW M2504100	2.5 x 4	0.47	145	Yellow
PUGY M2504100	2.5 x 4	0.47	145	Grey
PURD M2504100	2.5 x 4	0.47	145	Red
PUBK M0406100	4 x 6	0.59	130	Black
PUBE M0406100	4 x 6	0.59	130	Blue
PUCR M0406100	4 x 6	0.59	130	Clear
PUGN M0406100	4 x 6	0.59	130	Green
PUYW M0406100	4 x 6	0.59	130	Yellow
PUGY M0406100	4 x 6	0.59	130	Grey
PURD M0406100	4 x 6	0.59	130	Red
PUBK M5508100	5.5 x 8	0.79	123	Black
PUBE M5508100	5.5 x 8	0.79	123	Blue
PUCR M5508100	5.5 x 8	0.79	123	Clear
PUGN M5508100	5.5 x 8	0.79	123	Green
PUYW M5508100	5.5 x 8	0.79	123	Yellow
PUGY M5508100	5.5 x 8	0.79	123	Grey
PURD M5508100	5.5 x 8	0.79	123	Red
PUBK M0710100	7 x 10	0.98	123	Black

Reference	ID (/OD (mm))	Mini bend radius (at 68° F (in))	Max operating pressure (at 68° F (psi)	Color
PUBE M0710100	7 x 10	0.98	123	Blue
PUCR M0710100	7 x 10	0.98	123	Clear
PUBK M0812100	8 x 12	1.38	130	Black
PUBE M0812100	8 x 12	1.38	130	Blue
PUCR M0812100	8 x 12	1.38	130	Clear
PUBK M9514100	9.5 x 14	1.77	130	Black

