

## Polyurethane tube Ester base in 25 meter-box (unit of sales = 1 box)



<u>ID/OD (mm)</u> 2.5 x 4	<u>Mini bend radius (mm)</u> 12	<u>Max operating pressure (at 20°C (bar))</u> 10	<u>Colour</u> Black
<u>Temperature</u> - 20°C to +70°C	<u>Construction</u> Polyurethane Ester base	<u>Highlight</u> Resistant to oils and greases	

Description								
Reference	ID/OD (mm)	Mini bend radius (mm)	Max operating pressure (at 20°C (bar))	Colour	ID (/OD (mm)	Mini bend radius (at 68°F (in)	Max operating pressure (at 68°F (psi)	Color
<b>PUBK M250425</b>	2.5 x 4	12	10	Black	2.5 x 4	0.47	145	Clear

Reference	ID/OD (mm)	Mini bend radius (mm)	Max operating pressure (at 20°C (bar)	Colour	ID (/OD (mm)	Mini bend radius(at 68°F(in)	Max operating pressure (at 68°F (psi)	Color
<b>PUBE M250425</b>	2.5 x 4	12	10	Blue	2.5 x 4	0.47	145	Green
<b>PUCR M250425</b>					2.5 x 4	0.47	145	Yellow
<b>PUGN M250425</b>					2.5 x 4	0.47	145	Grey
<b>PUYW M250425</b>					2.5 x 4	0.47	145	Red
<b>PUGY M250425</b>					4 x 6	0.59	130	Black
<b>PURD M250425</b>					4 x 6	0.59	130	Blue
<b>PUBK M040625</b>					4 x 6	0.59	130	Clear
<b>PUBE M040625</b>					4 x 6	0.59	130	Green
<b>PUCR M040625</b>					4 x 6	0.59	130	Yellow
<b>PUGN M040625</b>					4 x 6	0.59	130	Grey
<b>PUYW M040625</b>					4 x 6	0.59	130	Red
<b>PUGY M040625</b>					5.5 x 8	0.79	123	Black

Reference	ID/OD (mm)	Mini bend radius (mm)	Max operating pressure (at 20°C (bar)	Colour	ID (/OD (mm)	Mini bend radius(at 68°F(in)	Max operating pressure (at 68°F (psi)	Color
PURD M040625					5.5 x 8	0.79	123	Blue
PUBK M550825					5.5 x 8	0.79	123	Green
PUBE M550825					5.5 x 8	0.79	123	Yellow
PUGN M550825					5.5 x 8	0.79	123	Grey
PUYW M550825					5.5 x 8	0.79	123	Red
PUGY M550825					7 x 10	0.98	123	Black
PURD M550825					7 x 10	0.98	123	Blue
PUBK M071025					7 x 10	0.98	123	Clear
PUBE M071025					7 x 10	0.98	123	Green
PUCR M071025					7 x 10	0.98	123	Yellow
PUGN M071025					7 x 10	0.98	123	Grey
PUYW M071025					7 x 10	0.98	123	Red

Reference	ID/OD (mm)	Mini bend radius (mm)	Max operating pressure (at 20°C (bar)	Colour	ID (/OD (mm)	Mini bend radius(at 68°F(in)	Max operating pressure (at 68°F (psi)	Color
<b>PUGY M071025</b>					8 x 12	1.38	130	Black
<b>PURD M071025</b>					8 x 12	1.38	130	Blue
<b>PUBK M081225</b>					8 x 12	1.38	130	Clear
<b>PUBE M081225</b>					9.5 x 14	1.77	130	Black
<b>PUCR M081225</b>					9.5 x 14	1.77	130	Blue
<b>PUBK M951425</b>					9.5 x 14	1.77	130	Clear
<b>PUBE M951425</b>					11 x 16	2.17	130	Black
<b>PUCR M951425</b>								
<b>PUBK M111625</b>								

Dimensions	
Reference	
	PUBK M250425
	PUBE M250425
	PUCR M250425
	PUGN M250425
	PUYW M250425
	PUGY M250425
	PURD M250425
	PUBK M040625
	PUBE M040625
	PUCR M040625
	PUGN M040625
	PUYW M040625
	PUGY M040625
	PURD M040625
	PUBK M550825
	PUBE M550825
	PUGN M550825
	PUYW M550825
	PUGY M550825
	PURD M550825
	PUBK M071025
	PUBE M071025

Reference
PUCR M071025
PUGN M071025
PUYW M071025
PUGY M071025
PURD M071025
PUBK M081225
PUBE M081225
PUCR M081225
PUBK M951425
PUBE M951425
PUCR M951425
PUBK M111625