

## STOFLEX hose with swivel regular coupling and rubber boot



<b><u>NPT male thread</u></b> 1/4" MNPT	<b><u>Diameter (ID (in))</u></b> 3/8"	<b><u>Coupler</u></b> URC 06	<b><u>Length (ft)</u></b> 4.5'
<b><u>Operating pressure</u></b> 29 to 174 psi	<b><u>Temperature</u></b> +5°F to +158°F		

Description				
Reference	NPT male thread	Diameter (ID (in))	Coupler	Length (ft)
<b>USTO 3804FA</b>	1/4" MNPT	3/8"	URC 06	4.5'
<b>USTO 3835FA</b>	1/4" MNPT	3/8"	URC 06	35'
<b>USTO 3850FA</b>	1/4" MNPT	3/8"	URC 06	50'
<b>ESTO 3804FA</b>	3/8" MNPT	3/8"	ERC 07	4.5'
<b>ESTO 3806FA</b>	3/8" MNPT	3/8"	ERC 07	6'
<b>ESTO 3835FA</b>	3/8" MNPT	3/8"	ERC 07	35'
<b>ESTO 3850FA</b>	3/8" MNPT	3/8"	ERC 07	50'

Reference	NPT male thread	Diameter (ID (in))	Coupler	Length (ft)
<b>ESTO 3875FA</b>		3/8"		75'

