

## Polyamide (Nylon) Tubing in 100 ft rolls



<b><u>OD (in)</u></b> 3/16 or 0.188	<b><u>ID (in)</u></b> 0.138	<b><u>Mini bend radius (at 70°F (in))</u></b> 0.625	<b><u>Max operating pressure (at 70°F (psi))</u></b> 320
<b><u>Color</u></b> Black	<b><u>Temperature</u></b> - 60°F to +200°F	<b><u>Construction</u></b> Polyamide PA 12	<b><u>Highlight</u></b> Excellent shape memory Highly resistant to chemicals

Description					
Reference	OD (in)	ID (in)	Mini bend radius (at 70°F (in))	Max operating pressure (at 70°F (psi))	Color
<b>PABK I1331100</b>	3/16 or 0.188	0.138	0.625	320	Black
<b>PABE I0918100</b>	1/8 or 0.125	0.080	0.375	420	Blue
<b>PABK I0918100</b>	1/8 or 0.125	0.080	0.375	420	Black

Reference	OD (in)	ID (in)	Mini bend radius (at 70°F (in))	Max operating pressure (at 70°F (psi))	Color
<b>PACR I0918100</b>	1/8 or 0.125	0.080	0.375	420	Clear
<b>PABE I1053100</b>	5/32 or 0.156	0.106	0.5	350	Blue
<b>PABK I1053100</b>	5/32 or 0.156	0.106	0.5	350	Black
<b>PACR I1053100</b>	5/32 or 0.156	0.106	0.5	350	Clear
<b>PACR I1331100</b>	3/16 or 0.188	0.138	0.625	320	Clear
<b>PABE I1814100</b>	1/4 or 0.250	0.180	1.25	290	Blue
<b>PABK I1814100</b>	1/4 or 0.250	0.180	1.25	290	Black
<b>PACR I1814100</b>	1/4 or 0.250	0.180	1.25	290	Clear
<b>PARD I1814100</b>	1/4 or 0.250	0.180	1.25	290	Red
<b>PABE I2351100</b>	5/16 or 0.313	0.236	1.496	250	Blue
<b>PABK I2351100</b>	5/16 or 0.313	0.236	1.496	250	Black
<b>PACR I2351100</b>	5/16 or 0.313	0.236	1.496	250	Clear
<b>PABE I1331100</b>	3/16 or 0.188	0.138	0.625	320	Blue

Reference	OD (in)	ID (in)	Mini bend radius (at 70°F (in))	Max operating pressure (at 70°F (psi))	Color
<b>PABE I2738100</b>	3/8 or 0.375	0.275	1.2	250	Blue
<b>PABK I2738100</b>	3/8 or 0.375	0.275	1.2	250	Black
<b>PACR I2738100</b>	3/8 or 0.375	0.275	1.2	250	Clear
<b>PARD I2738100</b>	3/8 or 0.375	0.275	1.2	250	Red
<b>PABE I3212100</b>	1/2 or 0.500	0.375	3.5	240	Blue
<b>PABK I3212100</b>	1/2 or 0.500	0.375	3.5	240	Black
<b>PACR I3212100</b>	1/2 or 0.500	0.375	3.5	240	Clear

