

Polyamide (Nylon) Tubing in 500 ft rolls



<u>OD (in)</u> 3/16 or 0.188	<u>ID (in)</u> 0.138	<u>Mini bend radius (at 68°F (in))</u> 0.625	<u>Max operating pressure (at 68°F (psi))</u> 320
<u>Color</u> Black	<u>Temperature</u> - 60°F to +200°F	<u>Construction</u> Polyamide PA 12	<u>Highlight</u> Excellent shape memory Highly resistant to chemicals

Description					
Reference	OD (in)	ID (in)	Mini bend radius (at 68°F (in))	Max operating pressure (at 68°F (psi))	Color
PABK I1331500	3/16 or 0.188	0.138	0.625	320	Black
PABE I0918500	1/8 or 0.125	0.080	0.375	420	Blue
PABE I1331500	3/16 or 0.188	0.138	0.625	320	Blue

Reference	OD (in)	ID (in)	Mini bend radius (at 68°F (in))	Max operating pressure (at 68°F (psi))	Color
PABK I0918500	1/8 or 0.125	0.080	0.375	420	Black
PACR I0918500	1/8 or 0.125	0.080	0.375	420	Clear
PABE I1053500	5/32 or 0.156	0.106	0.5	350	Blue
PABK I1053500	5/32 or 0.156	0.106	0.5	350	Black
PACR I1053500	5/32 or 0.156	0.106	0.5	350	Clear
PACR I1331500	3/16 or 0.188	0.138	0.625	320	Clear
PABE I1814500	1/4 or 0.250	0.18	1.25	290	Blue
PABK I1814500	1/4 or 0.250	0.18	1.25	290	Black
PACR I1814500	1/4 or 0.250	0.18	1.25	290	Clear

